

Rura karbowana typ 750N, bez pilota

Nr kat.	Wymiary ØA / ØB	Opakowanie	Typ	Materiał	Kolor	Temperatura pracy	Odporność na uderzenia	Uwagi
6109-25/750P	Ø16 / Ø11	25mb.	750N	PVC	czarny	od -25°C do +60°C	2J	Odporne na UV Nierozprzestrzeniające płomienia
6109-50/750P		50mb.						
6108-25/750P	Ø18 / Ø13,5	25mb.						
6108-50/750P		50mb.						
6100A-25/750P	Ø20 / Ø14,5	25mb.						
6100A-50/750P		50mb.						
6102A-25/750P	Ø25 / Ø19	25mb.						
6102A-50/750P		50mb.						
6110/750P	Ø32 / Ø25	25mb.						
6110-50/750P		50mb.						
6167-25/750	Ø40 / Ø33	25mb.						

Rura karbowana typ 750N, z pilotem

Nr kat.	Wymiary ØA / ØB	Opakowanie	Typ	Materiał	Kolor	Temperatura pracy	Odporność na uderzenia	Uwagi
6160-25/750P	Ø16 / Ø11	25mb.	750N	PVC	czarny	od -25°C do +60°C	2J	Z pilotem Odporne na UV Nierozprzestrzeniające płomienia
6160-50/750P		50mb.						
6162-25/750P	Ø18 / Ø13,5	25mb.						
6162-50/750P		50mb.						
6161A-25/750P	Ø20 / Ø14,5	25mb.						
6161A-50/750P		50mb.						
6163A-25/750P	Ø25 / Ø19	25mb.						
6163A-50/750P		50mb.						
6166-25/750P	Ø32 / Ø25	25mb.						
6166-50/750P		50mb.						
6168-25/750	Ø40 / Ø33	25mb.						

