

Nr kat.	Wymiary			Materiał	Palność UL94	Temperatura pracy (°C)	Min siła zrywu(kg)
	A	B	C				
H.7251B	100mm	2,5mm	22mm	Nylon 66	V-2	-35 ; +85	8
H.7252B	120mm	2,5mm	30mm	Nylon 66	V-2	-35 ; +85	8
H.7253B	140mm	2,5mm	33mm	Nylon 66	V-2	-35 ; +85	8
H.7254B	160mm	2,5mm	35mm	Nylon 66	V-2	-35 ; +85	8
H.7256B	140mm	3,6mm	33mm	Nylon 66	V-2	-35 ; +85	18
H.7263B	150mm	4,8mm	35mm	Nylon 66	V-2	-35 ; +85	22
H.7255B	200mm	2,5mm	53mm	Nylon 66	V-2	-35 ; +85	8
H.7257B	200mm	3,6mm	53mm	Nylon 66	V-2	-35 ; +85	18
H.7265B	200mm	4,8mm	53mm	Nylon 66	V-2	-35 ; +85	22
H.7266B	250mm	4,8mm	60mm	Nylon 66	V-2	-35 ; +85	22
H.7259B	300mm	3,6mm	76mm	Nylon 66	V-2	-35 ; +85	18
H.7268B	300mm	4,8mm	76mm	Nylon 66	V-2	-35 ; +85	22
H.7283B	350mm	4,8mm	83mm	Nylon 66	V-2	-35 ; +85	22
H.7261B	370mm	3,6mm	102mm	Nylon 66	V-2	-35 ; +85	18
H.7274B	370mm	7,6mm	102mm	Nylon 66	V-2	-35 ; +85	56
H.7271B	430mm	4,8mm	113mm	Nylon 66	V-2	-35 ; +85	22
H.7276B	550mm	7,6mm	145mm	Nylon 66	V-2	-35 ; +85	56
H.7285B	920mm	8,8mm	263mm	Nylon 66	V-2	-35 ; +85	78

W ofercie również opaski
w kolorze białym / półprzezroczystym

