

Nr kat.	Wymiary			Materiał	Palność UL94	Temperatura pracy (°C)	Min siła zrywu(kg)
	A	B	C				
H.7251	100mm	2,5mm	22mm	Nylon 66	V-2	-35 ; +85	8
H.7252	120mm	2,5mm	30mm	Nylon 66	V-2	-35 ; +85	8
H.7253	140mm	2,5mm	33mm	Nylon 66	V-2	-35 ; +85	8
H.7254	160mm	2,5mm	35mm	Nylon 66	V-2	-35 ; +85	8
H.7256	140mm	3,6mm	33mm	Nylon 66	V-2	-35 ; +85	18
H.7263	150mm	4,8mm	35mm	Nylon 66	V-2	-35 ; +85	22
H.7255	200mm	2,5mm	53mm	Nylon 66	V-2	-35 ; +85	8
H.7257	200mm	3,6mm	53mm	Nylon 66	V-2	-35 ; +85	18
H.7265	200mm	4,8mm	53mm	Nylon 66	V-2	-35 ; +85	22
H.7266	250mm	4,8mm	60mm	Nylon 66	V-2	-35 ; +85	22
H.7259	300mm	3,6mm	76mm	Nylon 66	V-2	-35 ; +85	18
H.7268	300mm	4,8mm	76mm	Nylon 66	V-2	-35 ; +85	22
H.7283	350mm	4,8mm	83mm	Nylon 66	V-2	-35 ; +85	22
H.7261	370mm	3,6mm	102mm	Nylon 66	V-2	-35 ; +85	18
H.7274	370mm	7,6mm	102mm	Nylon 66	V-2	-35 ; +85	56
H.7271	430mm	4,8mm	113mm	Nylon 66	V-2	-35 ; +85	22
H.7276	550mm	7,6mm	145mm	Nylon 66	V-2	-35 ; +85	56

W ofercie również opaski  
w kolorze czarnym

